尺寸:140x100mm
材质:128G铜板纸，单色印刷，折叠页

Alice98人体工学单模??键盘

—用户手册—

FEKER

产品参数

产品品牌：FEKER
产品名称：ALICE98
产品型号：Gasket结构
产品尺寸：405.7*156.9*42.5mm
产品重量：约1.5 g
键帽材质：ABS+p
连接方式：有线+2.4G
动作机制：Hot-Swap
接口：Type-C
电源容量：5000mA
电压：5V
数据线：Type-C to Type-C
兼容系统：Windows7/8/10/11/Mac/Linux

开关/指示灯说明

1.CAPS指示灯：CAPS键按下灯亮指示

2.Win锁指示：WIN键灯亮指示

3.Num指示灯：NUM键灯亮指示

灯光效果说明

1、上电后，灯光默认键盘最中心，每隔两下，两列向外扩散灯，每隔两格灯光状态。

2、灯光模式切换两秒钟常亮表示上电灯下，最后灯光模式会保存灯。

3、灯光常亮，闪烁灯等

键盘组装说明

装配顺序：固定弹簧→SV→EV+

按键复合功能键说明

组合按键	WIN功能	MAC功能（苹果键盘）	描述
Fn+F1	此电脑	屏幕亮度减	组合开关选择MAC / WIN
Fn+F2	主页	屏幕亮度加	
Fn+F3	计算器	多任务控制器	
Fn+F4	静音	调度中心	
Fn+F5	播放器	无	
Fn+F6	停止播放	无	
Fn+F7	上一曲	上一曲	
Fn+F8	暂停/播放	暂停/播放	
Fn+F9	下一曲	下一曲	
Fn+F10	静音	静音	
Fn+F11	音量	音量-	
Fn+F12	音量+	音量+	
Fn+BACK	锁键/下复位	锁键/下复位	键盘默认是WIN模式
Fn+L	键盘背光模式切换	键盘背光模式切换	按照WIN键的顺序切换
Fn+Enter	键盘背光灯光切换	键盘背光灯光切换	按照灯效，默认模式最亮

按键复合功能键说明

组合按键	WIN功能	MAC功能（苹果键盘）	描述
Fn+Alt/Shift	切换组合灯灯效	切换组合灯灯效	灯光可调/呼吸/常亮 默认灯效关
Fn+"/Num	切换键盘背光灯效	切换键盘背光灯效	灯光可调/呼吸/常亮 默认灯效关
Fn+T	键盘背光开关	键盘背光开关	常闭灯
Fn+WIN L	锁WIN	无	无
Fn+←	灯光模式变慢	灯光模式变慢	组合开关选择MAC / WIN
Fn+→	灯光模式变快	灯光模式变快	
Fn+↑	灯光亮度+	灯光亮度+	按照每组灯上下变化灯光的亮度
Fn+↓	灯光亮度-	灯光亮度-	
Fn+Ctrl	无	INS	
Fn+PgUP	HOME	HOME	
Fn+PgDN	END	END	

Product parameter

Product brand：FEKER
Product Name：ALICE98
Product structure: gasket structure
Product size：405.7*156.9*42.5mm
Product weight：1.5Kg
Number of keys：98Key
Connection method：Wired USB
Wire length：1.5M
Interface：Keyprint separation type C interface
Matrix：Full key no impact
Backlight：Full color RGB, 20 kinds of lighting effects
Compatibility：Windows7/8/10/11/Mac/Linux

Description of switch/indicator light

1.**Switch**indicator light: Left key indicator light is mainly white light

2.**Lock win**indicator: Win key indicates white light.

3.**NUM**indicator: Num key indicates white light.

Lighting effect description

1. After power-on, the light runs around the keyboard, and the tail goes out. After running all the keys, the light status before power-off is restored.
2. Lighting mode lighting order according to the table from top to bottom, finally cut the mode after OFF.
3. 41 sets of lighting effects

Knob Function Description

Knob detail: press is equivalent to single click.

Key compound function description

Combination buttons	With function	MAC function (single press trigger)	Describe
Fn+F1	This computer	Screen brightness decrease	Flip the switch to select MAC/WIN
Fn+F2	Homepage	Screen brightness increase	
Fn+F3	Calculator	Multi-task controller	
Fn+F4	Mute	Keyboard Mute	
Fn+F5	Player	Nothing	
Fn+F6	Stop playing	Nothing	
Fn+F7	Previous song	Previous song	
Fn+F8	Play/Pause	Play pause	
Fn+F9	Next song	Next song	
Fn+F10	Mute	Mute	
Fn+F11	Volume -	Volume -	
Fn+F12	Volume +	Volume +	
Fn+BACKSPACE	Short press to reset.	Short press to reset.	Keyboard backlight goes out once
Fn+C	Keyboard backlight color switching	Keyboard backlight color switching	Order: Monochrome Cycle Gradient

Key compound function description

Combination buttons	With function	MAC function (single press trigger)	Describe
Fn+Esc	Lock WIN	Keyboard backlight effect switching	All lighting effects, default is follow the first
Fn+"/Num	Switching break mice value or scroll wheel	Keyboard backlight switch	Drivemen Spectrum Breathing Mieyo On/Off. Default Drivemen
Fn+T	Keyboard backlight switch	...	
Fn+WIN L	Lock WIN	Light speed slows down	With memory
Fn+←	Light speed slows down	Accelerated lighting speed	
Fn+→	Accelerated lighting speed	Accelerated lighting speed	
Fn+↑	Lightning brightness+	Lightning brightness+	When in the extreme gear position, the up, down, left, and right keys flash three times. To indicate
Fn+↓	Lightning brightness-	Lightning brightness-	To indicate

Key compound function description

Combination buttons	With function	MAC function (single press trigger)	Describe
Fn+INS	INS	INS	
Fn+PgUP	HOME	HOME	
Fn+PgDN	END	END	

产品质保

感谢您对FEKER产品的信任和支持，为了正常的心情用产品，请仔细阅读以下内容。

按照用户指南中的内容操作和使用，以下情况：

1、操作有误情况：请按正确的步骤操作以下内，例如，键盘，软件不连接情况等。

2、电池问题：请按照产品使用说明书的要求进行充电，例如，电池不能充电等。

3、产品不能使用情况：

a.因操作有误导致不能使用的情况；

b.有使用工具拆卸情况，例如，螺丝，螺帽，弹片，电池，不在合格证等；

c.一切人为因素，进行拆卸，涂改标，撕毒不全等，不在保修范围。

更多产品信息请浏览

FEKER官网

https://www.feknorgaming.com

质保卡

产品型号：_____

购买日期：_____

客户姓名：_____

联系电话：_____

联系地址：_____

执行标准：GB/T 24401-2010